


1	DB7	DATA BUS 7
2	DB6	DATA BUS 6
3	DB5	DATA BUS 5
4	DB4	DATA BUS 4
5	DB3	DATA BUS 3
6	DB2	DATA BUS 2
7	DB1	DATA BUS 1
8	DB0	DATA BUS 0
9	E1	Enable signal for KS0066 (1)
10	R/W	H: Read; L: Write
11	RS	Register select
12	VO	Contrast adjust
13	VSS	Power ground
14	VDD	Power supply (+5V)
15	E2	Enable signal for KS0066 (2)
16	NC	No connection
17	A	Backlight (+) +5V
18	K	Backlight (-)

NOTES:

1. DISPLAY TYPE: STN, YELLOW-GREEN
2. POLARIZER TYPE: TRANSPARENT, POSITIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -20°C~+70°C
5. STORAGE TEMPERATURE: -30°C~+80°C
6. VDD: +5V
7. DRIVE METHOD: 1/16DUTY, 1/5BIAS
8. CONTROLLER: S6A0069
9. BACKLIGHT TYPE: YELLOW-GREEN, BOTTOM
10. BACKLIGHT SUPPLY VOLTAGE: +5.0V
11. VOP: TBD

 WAYING (HONGKONG) SHARES LIMITED	
DESIGN:	MODEL NUMBER: WYM4004A
CHECK:	VERSION: A
APPROVE:	SHEET: 1 OF 1
Unspecified tolerances are ±0.3	
UNITS: MM	DATE: 2007-03-25

