



PIN	1	2	3	4	5	6	7	8	9	10	11	12	13
SYMBOL	ESD	VLCD	VS+	VS-	VBO-	VBI-	VBI+	VBO+	VDD	VSS	TS14	BMO	CS0
PIN	14	15	16	17	18	19	20	21	22	23	24	25	26
SYMBOL	CD	WRI	WRO	RST	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	ESD

1. DISPLAY TYPE: FSTN
2. VIEWING DIRECTION: 6:00
3. POLARIZER MODE: TRANSPARENTIVE/POSITIVE
4. IC: LC1698U
5. OPERATING TEMP: -20° C~+70° C
6. STORAGE TEMP: -30° C~+80° C
7. Drive Method: 1/160duty 1/10bias
8. LCD OPERATING VOLTAGE: 16.5V
9. BACKLIGHT VOLTAGE: 3.0V
10. UNMARKED TOLERANCES: ±0.3mm
11. REQUIREMENT ON ENVIRONMENTAL PROTECTION: ROHS

**Waying Waying (HONGKONG) SHARES LIMITED**

DRAWN BY:	TITLE: WYM160160K1G	UNIT: mm
ME CHECKED BY:	DWG NO: G-1	SCALE: 1 OF 1
FE CHECKED BY:	DATE: 2013.04.09	SHEET NO: 1 OF 1