



1	FG	Frame ground
2	VSS	Power ground
3	VDD	Power supply (+5V)
4	VO	Contrast adjust
5	/WR	Write signal
6	/RD	Read signal
7	/CE	Chip enable for T6963C
8	C/D	H: Command; L: Data
9	NC	No connection
10	/RST	Reset signal
11	DB0	DATA BUS 0
12	DB1	DATA BUS 1
13	DB2	DATA BUS 2
14	DB3	DATA BUS 3
15	DB4	DATA BUS 4
16	DB5	DATA BUS 5
17	DB6	DATA BUS 6
18	DB7	DATA BUS 7
19	FS	Font type. L:8x8; H:8x8
20	VO/UT	Internal DC-DC converter output
21	A	Backlight (+) +5V
22	K	Backlight (-)

**NOTES:**

1. DISPLAY TYPE: STN,BLUE
2. POLARIZER TYPE: TRANSMISSIVE,NEGATIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -20°C~+70°C
5. STORAGE TEMPERATURE: -30°C~+80°C
6. VDD: +5V
7. DRIVE METHOD: 1/128DUTY,1/12BIAS
8. CONTROLLER: T6963C
9. BACKLIGHT TYPE: WHITE,SIDE
10. BACKLIGHT SUPPLY VOLTAGE: +5.0V
11. VOP: 14.5V



WAYING (HONGKONG) SHARES LIMITED

DESIGNER:	MODEL NUMBER:	UNITS:	MM
CHECK:	WYM240128E-GRTSESWD-0000	VERSION:	A
APPROVE:		SHEET:	1 OF 1
Unspecified tolerances are ±0.3		DATE:	2006-03-18