



1	FG	Frame ground
2	VSS	Power ground
3	VDD	Power supply (+5V)
4	VO	Contrast adjust
5	/WR	Data write
6	/RD	Data read
7	/CE	Chip Enable for T6963C
8	C/D	H: Command; L:Data
9	NC	No connection
10	/RST	Reset signal
11-18	DO-D7	DATA BUS
19	FS	Font type. L:8X8; H:6X8
20	VO _{UT}	Negative power output
21	A	Backlight (+) +5V
22	K	Backlight (-)

NOTES:

1. DISPLAY TYPE: STN, YELLOW-GREEN
2. POLARIZER TYPE: TRANSPARENT, POSITIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -20°C~+70°C
5. STORAGE TEMPERATURE: -30°C~+80°C
6. VDD: +5V
7. DRIVE METHOD: 1/64DUTY, 1/9BIAS
8. CONTROLLER: T6963C
9. BACKLIGHT TYPE: YELLOW-GREEN
10. BACKLIGHT SUPPLY VOLTAGE: +5.0V
11. VOP: TBD

WYING WAYING (HONGKONG) SHARES LIMITED

DESIGN: MODEL NUMBER: UNITS: MM

CHECK: WYM24064B VERSION: A

APPROVE: SHEET: 1 OF 1

Unspecified tolerances are ±0.3 DATE: 2008-09-17