


1. DISPLAY TYPE: FSTN
2. VIEWING DIRECTION: 6:00
3. POLARIZER MODE: TRANSPARENT/POSITIVE
4. I.C: ST75161
5. OPERATING TEMP: -40° C-+70° C
6. STORAGE TEMP: -40° C-+80° C
7. Drive Method: 1/160duty 1/10bias
8. LCD OPERATING VOLTAGE: 15.5V
RECOMMEND VDD= 3.3V
9. BACKLIGHT VOLTAGE: 3.0V
10. UNMARKED TOLERANCES: ±0.3mm
11. REQUIREMENT ON ENVIRONMENTAL PROTECTION: ROHS



DETAIL A: (10:1)

INTERFACE

NO.	SIGNAL
1	ESD
2	VG
3	NC
4	V0
5	XV0
6	CA1+
7	CA1+
8	NC
9	VDD
10	VSS
11	COMSN
12	TF2
13	TF1
14	TF0
15	CSB
16	A0
17	ERD
18	RWR
19	RSTB
20-27	DO-D7
28	EXTB
29	VPP
30	ESD

Waying (HONGKONG) SHARES LIMITED

DRAWN BY:	TITLE: WYM160160K12G	UNITS: mm
ME CHECKED BY:	DWG NO: G-1	
EE CHECKED BY:	SCALE:	SHEET NO: 1 OF 1
DATE: 2021.09.30		